



# MAX Adapter

State-of-the-art Cellular Modem at a breakthrough price point



### Built to Last

Sturdy industrial-strength designed for continuous high-traffic operation.



### Portable

The light and sleek enclosure offers portability in the palm of your hands.



### Compatible with 5G

Meet the ever increasing connectivity needs with the MAX Adapter 5G.



### Stay Connected


With two SIM slots, the MAX Adapter always has a way to connect.



## SpeedFusion Connect LTE/5G

With a built-in eSIM, achieving on-demand data to minimize data wastage and optimize your connectivity is simple. Do not settle for less, choose SpeedFusion Connect LTE/5G.

[→ Learn more](#)



# Connect with

## Peplink Products

Protect and reinforce products<sup>^</sup> with a USB port and make it a 5G/LTE WAN.



## Windows & Linux\* Devices

Providing 5G/LTE connectivity for Windows and Linux devices on-the-go.



## Non-Peplink Devices

Place anywhere to optimize cellular reception, reduce truck rolls, expand infrastructure, and maximize uptime for businesses that require always-on connectivity.



<sup>^</sup> For compatible models, please refer to the MAX Adapter [product page](#).

\* For users on the Linux, please refer to our MAX Adapter [user manual](#) to set up.



1x 5G Modem

## Specifications

<b>Cellular WAN Interfaces</b>	Single 5G Modem	<b>Operating Temperature</b>	-40° – 149°F / -40° – 65°C
<b>Redundant SIM Slot</b>	Yes	<b>Humidity</b>	15% – 95% (non-condensing)
<b>Downlink/ Uplink Datarate</b>	5G: 4 Gbps / 700 Mbps LTE CAT-20: 2 Gbps / 150 Mbps	<b>Warranty</b>	1-Year Limited Warranty
<b>Antenna Connectors</b>	4x SMA Cellular	<b>Certifications</b>	FCC, CE, IC
<b>Power Input</b>	5V USB-C	<b>Package Content</b>	MAX Adapter 5G, 4x LTE/5G LTE Antennas (ACW-235), USB-C Female to USB-A Male Adapter, USB-C Power Cable
<b>Power Consumption</b>	5W (nominal), 8W (max.)		
<b>Dimensions</b>	3.9 x 2.8 x 0.7 inches / 100 x 71 x 18.4 mm		
<b>Weight</b>	120g		

## Ordering Information

Product Code	Carrier / Category	5G Bands	LTE Bands
MAX-ADP-5GH-T	Global / 5G  <small>US Carrier Certifications: AT&amp;T, T-Mobile, US Cellular, Verizon (C-Band), FirstNet</small>	<b>5G (NSA) Sub 6Ghz:</b> n1, n2, n3, n5, n28, n41, n66, n71, n77, n78, n79	B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B32, B34, B38, B39, B40, B41, B42, B46, B48, B66, B71



## Specifications

<b>Cellular WAN Interfaces</b>	Single LTE Modem	<b>Operating Temperature</b>	-40° – 149°F / -40° – 65°C
<b>Redundant SIM Slot</b>	Yes	<b>Humidity</b>	15% – 95% (non-condensing)
<b>Downlink/ Uplink Datarate</b>	CAT-12: 600 Mbps / 150 Mbps CAT-6: 300Mbps / 50Mbps	<b>Warranty</b>	1-Year Limited Warranty
<b>Antenna Connectors</b>	2x SMA Cellular, 1x SMA GPS	<b>Certifications</b>	FCC, IC
<b>Power Input</b>	5V USB-C	<b>Package Content</b>	MAX Adapter, 2x LTE Antennas (ACW-813), USB-C Female to USB-A Male Adapter, USB-C Power Cable
<b>Power Consumption</b>	5W (nominal), 8W (max.)		
<b>Dimensions</b>	3.9 x 2.8 x 0.7 inches / 100 x 71 x 18.4 mm		
<b>Weight</b>	120g		

## Ordering Information

Product Code	Carrier / Category	LTE Bands	3G Bands
MAX-ADP-LTEA-K-T	Global CAT-12	B1, B2, B3, B4, B5, B7, B8, B9, B12, B13, B18, B19, B20, B26, B28, B29, B30, B32, B41, B42, B43, B46, B48, B66	HSPA+: B1, B2, B4, B5, B6, B8, B9, B19
MAX-ADP-LTEA-R-T	America CAT-12  US Carrier Certifications: AT&T, Verizon, FirstNet	B1, B2, B3, B4, B5, B7, B8, B9, B12, B13, B14, B18, B19, B20, B26, B29, B30, B32, B41, B42, B43, B46, B48, B66	HSPA+: B1, B2, B4, B5, B6, B8, B9, B19
MAX-ADP-LTEA-W-T	Global CAT-6	B1, B2, B3, B4, B5, B7, B8 , B12, B13, B20, B25, B26, B29, B30, B41	WCDMA/HSPA+/DC-HSPA+: B1, B2, B3, B4, B5, B8

## Accessories

Product Code	Description
ACW-232	GPS Antenna